

KS30 series - Kitemarked, pavior infill

PETER SAVAGE 'SHILTON' KITEMARKED RANGE

Kitemarked Fabricated Steel Recessed for Pavior Infill Access Cover & Frames

Product & load rating code:

KS30A	Class A15	1.5 Tonne
KS30B	Class B125	12.5 Tonne
KS30C	Class C250*	25 Tonne
KS30D	Class D400*	40 Tonne

Recess size code (R):

70mm recess (to suit 50mm blocks)	/70
100mm recess (to suit 80mm blocks)	/100

Product size suffix:

B - 450 x 450mm	F - 750 x 750mm
C - 600 x 450mm	G - 900 x 600mm
D - 600 x 600mm	J - 900 x 900mm
E - 750 x 600mm	

BS EN124, KM 38475

Non-standard sizes available

* Recommended for slow moving traffic applications only.



BS EN124, KM 38475

KS30 series features:

- Recessed lid for block paving/slab infill • Solid Base Plate • Angled inner section to aid removal •
- Heavy gauge lifting eyes pierced to accept standard profile lifting keys • All mild steel assembly •
- Underbraced to meet the relevant BS EN124 loading category •
- Lid supported and set into a substantial frame •
- Manufactured under an ISO 9001:2000 Quality System •

Finish: Hot dipped galvanised to BS EN ISO 1461 as standard.

Optional extras: locking screws, M.O.D. approved locking screws, rubber seals, badging i.e. WATER, GAS, ELEC etc.

Specification / Ordering:

Please choose the required load rating product code, size reference suffix, stating any optional extras i.e. KS30CG/70.

** Loading class C250 & D400 are supplied locked as standard

Nuneaton TEL : +44 (0) 24 7664 1777 **FAX** : +44 (0) 24 7637 5250 **EMAIL** : sales@peter-savage.co.uk

Wakefield TEL : +44 (0) 1924 258 381 **FAX** : +44 (0) 1924 258 382 **EMAIL** : wakefield@peter-savage.co.uk